



# Meyors Chemical INC Limited

Operational Office Address: Suite 2610-2611 Foreign Trade Building, 239 Zhongxing Road, Luohu District, Shen Zhen City, P R of China

> Tel: +86-755-8218 4166 Fax: +86-755- 8218 7033 Email: info@meyor.cn URL: www.rbb.com.cn

## **DATA-SHEET**

SPECIFICATIO	ON & DATA	Chemical Analysis:		
SHEET		化学分析		
物质规格数据表				
Product Code:	DA0075 4 000 40	Chemical Name:	Hexamethylene-1,6-bis(thiosulfate),disodi um salt,dihydrate	
产品编码	PA0275 1 000 42	化学名称	二水合六亚甲基-1,6-二硫代硫酸二钠盐	
Trade Name:	Duralink HTS	CAS No.:	5719-73-3	
商品名称	抗返原剂	CAS 编号:		
Synonym	LITO			
同类名称	HTS			

Product Information: 产品资料

#### \*\*\*Specification 规格

Appearance (visual inspection): 外观(目测)	White powder 白色粉末	Assay Content%≥ 纯度%≥	98
Assay (titration)%min 滴定%	95.0	Additive (%): 附加值:%	1.0 – 2.0
Chloride as NaCl%max≤ 氯化物含量%≤	0.5	Moisture % 湿度 %	8.5-10.0

#### \*\*\*Typical Properties 主要特性

This is a compensatory sulphide fertilizer materials to enhance capability of antireversion, its unique chemical structure that in response to alum rubber large molecules in the chain connecting the sulphur bond between embedded in the six methylene a pliable agglomerate, a "composite" to the structure. The structure may be the key to effectively improve the thermal stability of the glue to the original nature of resistance. In addition enhances the keys to the pliable nature can greatly improve sulphide plastic in a dynamic conditions flexibleness can.

本品是一种补偿性硫化助剂,用来提高抗返原性能, 其独特的化学结构使其在硫化反应中能够在连接橡胶大 分子主链的硫键之间嵌入柔顺的六亚甲基基团,形成"复 合"的交联结构。这种结构可有效改善交联键的热稳定 性,使胶料的抗返原性提高。此外还能提高交联键的柔 顺性,能够大大改善硫化胶在动态条件下的屈挠性能。

#### \*\*\*Recommended Applications 应用推荐

As NR,IR,NBR and secondary cure stabilizer of their mixed micelle,as adhesive additive when adhere with brassed steel wire cord.

用作 NR、IR、NBR 及它们的共混胶的二次硫化稳定剂和与镀黄铜钢丝进行粘接时作为粘结添加剂。

### \*\*\*Handling and Storage recommendations

Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Store in a cool, dry place. Keep container closed when not in use.

避免与眼睛、皮肤和衣物接触。避免摄取或吸入。 储存在阴凉干燥处。产品不用是应密封。

#### \*\*\*Package 包装

Bag: 25kg/bag	Pallet(1.1*1.1*0.1): 600KG/Pallet
包装: 25kg/bag	托盘(1.1*1.1*0.1): 600KG/托